



TE640Z3F-WTM2-AP | C6A,LSFRZH,4/23,FTP,WT
Copper Twisted Pair Cable, Category 6A, 4-pair, shielded F/UTP, 300 m, white

Body Features

Cable Configuration	F/UTP
Conductor Material	Solid bare copper
Jacket Color	White
Insulation Material	PE
Shield Material	Aluminum
Shield Type	Overall foil

Configuration Features

Number of Conductors	8
Number of Pairs	4

Dimensions

Overall Outside Diameter	7.200 mm 0.283 in
Length	305.000 m 1000.656 ft
Wire Size (CMA)	23 AWG

Industry Standards

Flammability Rating	LSFRZH
---------------------	--------

Packaging Features

Packaging Method	Reel
------------------	------

Product Availability

Region	Asia Latin America
--------	----------------------

Product Type Features

Product Type	Cable
System	None
Cable Style	Multi-Pair
Cable Type	Twisted Pair
Performance Category	Category 6A
Product Classification	Cable - TIA/EIA Category
Shielded	Yes
Wire/Cable Type	Twisted Pair

Usage Conditions

TE640Z3F-WTM2-AP | C6A,LSFRZH,4/23,FTP,WT

Operating Temperature Range -20 – 60 °C | -4 – 140 °F

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU

Classification

Compliant